

## SPECIFICATIONS MA4E Q9

		QUADRICYCLE	REMARKS	
		Frameless Body,fully colsed metal structure,5 doors 4		
OVER-ALL DEMENSIONS	(L*W*H)	3090x1420x1480		
	WHEELBASE	2170		
	TRACK FRONT	1215		
	TRACK REAR	1235		
	FRONT OVERHANG	464		
	REAR OVERHANG	451		
PASSENGER		PERSON	4	
WEIGHT	CURB WEIGHT		500	
	LOADING CAPACITY		300	
	BATTERY	kg	324	
TRAFFICABILITY	APPROACHING ANGEL		30	
	DESCENT ANGEL	( ° )	42	
	MIN TURNING RADIUS		4440	
	MIN GROUND CLEARANCE	mm	≥130	
POWER	7.5 kw 72v AC	CONTROLLER	SEVCOM	* Range and speed will vary depending on temperature, terrain, driving style, road conditions, or vehicle payload.
		MAX SPEED	65KM/H	
		DISTANCE PER CHARGE	120-180KM	
		RATED POWER	7.5KW	
		MAX CLIMBING CAPACITY	30%	
		MAX POWER	12.5KM	
		MAX TORQUE	150N.M	
BATTERY	TYPE	LEAD-ACID BATTERY		
	CAPACITY	72V 150AH 9PCS		
	CHARGE TIME	6-8 HOURS		
CHARGER	V/A	72 / 25		
STEERING	RACK & PINION			
TRANSMISSION	CVT			
BRAKE SYSTEM	TYPE	DUAL-CIRCUIT HYDRAULIC SYSTEM		
	SERVICE BRAKE	THE FRONT: DISC BRAKE/ REAR WHEEL: DRUM BRAKE		
	PARKING BRAKE	HAND MECHANIC,FORCE ON REAR TYRE		
SUSPENSION	FRONT SUSPENSION	MC PHERSON'S		
	REAR SUSPENSION	TORSION BEAM TYPE		
TYRE	SPEC.		145/70-R12	
	PRESSURE	KPa	350	
NOISE	MAX. NOISE	Db	≤70	
SHAFT	BALL CAGE TYPE DRIVE SHAFT			